

# Technical information

## Vescom 1000

---

2020

### application

Ready mixed wallcovering adhesive for hanging vinyl wallcovering of up to 370 g/m<sup>2</sup> with a paper or textile backing.

### substrate

Plastered walls, wood and wood-like materials, plasterboard, concrete, etc. are suitable if clean, dry, firm and flat.

### specific properties

Adhesive type	: Starch and resin dispersion-based adhesive
Brookfield viscosity:	: 32,500 mPa.s (HAT; spindle 6; 20 rpm; 20°C)
Dry solids content	: 22.0%
pH	: 7.5
Colour	: White
Open time	: 15 – 45 minutes
Bonding time	: 1 – 4 hours
Spreading rate	: 150 – 400 g/m <sup>2</sup>

VOS EU limit value: The limit values of this product is < 1 g/l VOS in accordance with Directive 2004/42/EC.

The open and bonding time and spreading rate will depend on the substrate, the wallcovering type and the temperature and relative humidity of the materials and the environment.

### application

Vescom 1000 is ready for use.

The adhesive can be applied on the substrate by using a (lamb's wool) roller or paintbrush.

### cleaning

Non-dried-on adhesive can be easily cleaned using water.

### packaging

10 ltr bucket

### storage and shelf life

The adhesive must be stored unopened preferably at room temperature. The product can be used as normal after defrosting and stirring correctly after freezing (up to -10 °C).

The shelf life of the product is 9 months.