

Technical information

Vescom 2000

2020

application

Vescom 2000 is a universally applicable wallcovering adhesive for hanging textile wallcovering and vinyl wallcovering heavier than 370 g/m² with a paper or textile backing.

Vescom 2000 prevents the "bubbling" of the wallcovering material on the wall. Due to the high wet adhesion power of the adhesive, it is suitable for heavy duty wallcovering materials.

substrate

For interior application to stuccowork, wood and wood-like materials, plasterboard, concrete, etc. are suitable if clean, dry, firm and smooth.

specific properties

Adhesive type	: Pasty starch and resin dispersion-based adhesive
Brookfield viscosity:	: 23,000 mPa.s (HAT; spindle TD; 5 rpm; 20°C)
Dry solids content	: 27.5%
pH	: 7.5
Colour	: White
Open time	: 15 – 45 minutes
Bonding time	: 1 – 4 hours
Spreading rate	: 150 – 400 g/m ²

VOS EU limit value: The limit values of this product is < 1 g/l VOS in accordance with Directive 2004/42/EC.

The open and bonding time and spreading rate will depend on the substrate, the wallcovering type and the temperature and relative humidity of the materials and the environment.

application

Vescom 2000 is ready for use.

The adhesive can be applied on the substrate by using a (lamb's wool) roller or paintbrush.

cleaning

Non-dried-on adhesive can be easily cleaned using water.

packaging

10 ltr bucket

storage and shelf life

The adhesive must be stored in a closed pack at, room temperature. The product can be used as normal after defrosting and stirring correctly after freezing (up to -10 °C).

The shelf life of the product is 9 months.