



Report Number: 18-001297 Revision Number:1 Date Order Received: 03/01/2018

For the Account of:

Vescom America Inc. 2289 Ross Mill Road Henderson, NC 272537

Burton 7056 Test #603

Client's Identification:

CERTIFICATE OF TESTING

TEST PERFORMED: Pilling Resistance and Other Related Surface Changes of Textile Fabrics: Brush Pilling Tester ASTM D3511/D3511M-16

TEST RESULTS

	Rating
Left	4.0
Center	4.0
Right	4.0
Average Rating	4.0

severe fuzz

RATING SYSTEM

Class 5.0	No Pilling	
Class 4.0	Slight Pilling	
Class 3.0	Moderate Pilling	
Class 2.0	Severe Pilling	
Class 1.0	Very Severe Pilling	
NOTES		
Test Conditions:		70 ±4°F, 65 ±5% Relative Humidity
Sampling Me	thod:	As Received
Viewing Apparatus:		Macheth Lightbooth

Sampling Method:	As Received
Viewing Apparatus:	Macbeth Lightbooth
Viewing Option:	45 degree
Rating Standard:	ADJD3512 Photographic Standards
Running Times:	4 minutes brushing / 2 minutes pilling

ACCEPTANCE CRITERIA

A.C.T. Standard:	Acceptance Criteria
Upholstery	Class 3 minimum

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

ata Stiver

Authorized Signature

553 76th Street, Byron Center, MI 49315

P: 616-559-6123 E: testlab@applied-textiles.com

Page 1 of 1

Date Order Completed: 03/05/2018

This laboratory test is not intended to reflect fabric performance under actual conditions. The certification procedure merely measures the performance of samples under the predetermined and specific test conditions prescribed by the standard specified. This certificate applies only to the standards or processing identified and to the random sample(s) tested. The test results are representative of the qualities of the piece or lot only to the standards or processing identified and to the random sample(s) tested. The test results are representative of the qualities of the piece or lot only to the extent the sample tested is representative of the piece or lot.

Our reports and letters are for the exclusive use of the customer to whom they are addressed and they and the corporation named on the reverse are not to be used under any circumstances without prior written approval. Samples will not be retained, unless specified by the customer. Retained samples will be kept a maximum time of one year unless a specific retention period is necessary.