

Vescom BV  
Sint-Jozefstraat 20  
5753 AV Deurne  
Nederland



Your notice of  
25-09-2017

Your reference

Date  
06-10-2017

## Analysis Report 17.05457.02

Required tests :

**BS 5867-2 (2008)**

| Identification number | Information given by the client | Date of receipt |
|-----------------------|---------------------------------|-----------------|
| T1720193              | Bray + print - 8065             | 25-09-2017      |

Gina Créelle

Order responsible

This report may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel.  
The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.  
In assessing compliance with the specifications, we did not take into account the uncertainty on the test results.

**CENTEXBEL • textile competence centre • www.centexbel.be • www.vkc.be**  
Inrichting erkend bij toepassing van de besluitwet van 30-01-1947 • Établissement reconnu par application de l'arrêté-loi du 30-01-1947  
GENT • Technologiepark 7 • BE-9052 Zwijnaarde, Belgium • phone +32 9 220 41 51 • fax +32 9 220 49 55 • gent@centexbel.be  
GRÂCE-HOLLOGNE • Rue du Travail 5 • BE-4460 Grâce-Hollogne, Belgium • phone +32 4 296 82 00 • g-h@centexbel.be  
KORTRIJK • Etienne Sabbelaan 49 • BE-8500 Kortrijk, Belgium • phone +32 56 281828 • fax +32 56 281830 • info@vkc.be  
VAT BE 0459.218.289 • IBAN BE44 2100 4729 6545 • BIC GEBABEBB

**Reference: T1720193 - Bray + print - 8065**

**Determination of the flammability of textile fabrics for curtains and drapes**

Date of ending the test 05-10-2017  
 Standard used EN ISO 15025 (2002)  
 Product standard BS 5867-2 (2008)

Deviation from the standard -

Conditioning 20°C, relative humidity 65%

The test specimens have not been cleaned nor submitted to an accelerated ageing procedure.

Tested side Front

Flame application time (s) 15

|                         | Length |    |    | Width |    |    |
|-------------------------|--------|----|----|-------|----|----|
|                         | 1      | 2  | 3  | 1     | 2  | 3  |
| Flame or hole on edge   | no     | no | no | no    | no | no |
| Flaming debris droplets | no     | no | no | no    | no | no |

Type B performance requirements

No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge.

There shall be no separation of any flaming debris droplets

Conclusion Flammability complies with the requirements of BS 5867-2:2008, type "B"