



Report Number: 19-000714 Revision Number:1 Date Order Received: 02/08/2019

For the Account of:

Vescom, B.V. Sint Jozestraat 20 5753 Av Duerne

Client's Identification:

Lani 7060 test729

CERTIFICATE OF TESTING

TEST PERFORMED: Pilling Resistance and Other Related Surface Changes of Textile Fabrics: Brush Pilling Tester ASTM D3511/D3511M-16

TEST RESULTS

	Rating
Left	2.5
Center	2.5
Right	2.5
Average Rating	2.5

RATING SYSTEM

Test Condition	ons:	70 ±4°F, 65 ±5°
NOTES		
Class 1.0	Very Severe F	Pilling
Class 2.0	Severe Pilling	
Class 3.0	Moderate Pilli	ng
Class 4.0	Slight Pilling	
Class 5.0	No Pilling	

Test Conditions:	70 ±4°F, 65 ±5% Relative Humidity
Sampling Method:	As Received
Viewing Apparatus:	Macbeth Lightbooth
Viewing Option:	45 degree
Rating Standard:	ADJD3512 Photographic Standards
Running Times:	4 minutes brushing / 2 minutes pilling

ACCEPTANCE CRITERIA

A.C.T. Standard:	Acceptance Criteria
Upholstery	Class 3 minimum

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Berta Stiver

Authorized Signature

553 76th Street, Byron Center, MI 49315

P: 616-559-6123 E: testlab@applied-textiles.com

Page 1 of 1

Date Order Completed: 02/16/2019

This laboratory test is not intended to reflect fabric performance under actual conditions. The certification procedure merely measures the performance of samples under the predetermined and specific test conditions prescribed by the standard specified. This certificate applies only to the standards or processing identified and to the random sample(s) tested. The test results are representative of the qualities of the piece or lot only to the standards or processing identified and to the random sample(s) tested. The test results are representative of the qualities of the piece or lot only to the extent the sample tested is representative of the piece or lot.