

# Technical information

## Vescom 3000

---

2020

### application

Vescom 3000 is a wallcovering adhesive for renovation projects where new wallcovering material is installed over different types of wallcovering including PVC.

### substrate

Permanent sealed (not breathing) surfaces.

### specific properties

Adhesive type	: Resin- and starch-based dispersion adhesive
Brookfield viscosity:	: 37,500 mPa.s (HAT; spindle 6; 20 rpm; 20°C)
Dry solids content	: 62.0%
pH	: 7.5
Colour	: White
Open time	: 15 – 45 minutes
Bonding time	: 1 – 4 hours
Spreading rate	: 150 – 400 g/m <sup>2</sup>

VOS EU limit value: The limit values of this product is < 1 g/l VOS in accordance with Directive 2004/42/EC.

The open and bonding time and spreading rate will depend on the substrate, the wallcovering type and the temperature and relative humidity of the materials and the environment.

### application

Vescom 3000 is ready for use, (do not dilute).

The adhesive can be applied on the substrate by using a (lamb's wool) roller or paintbrush.

The substrate must be clean, dry, firm and smooth.

### cleaning

Non-dried-on adhesive can be easily cleaned using water.

### packaging

10 ltr bucket

### storage and shelf life

The adhesive must be stored in a unopened pack preferably at room temperature.

The product can be used as normal after defrosting and stirring correctly after freezing (up to -10 °C).

The shelf life of the product is 9 months.