

P.O. Box 554 | 2665 ZN Bleiswijk Brandpuntlaan Zuid 16 | 2665 NZ Bleiswijk The Netherlands +31 88 3473 723 nederland@efectis.com

CLASSIFICATION

CLASSIFICATION OF REACTION TO FIRE PERFORMANCE IN ACCORDANCE WITH EN 13501-1:2007+A1:2009

Classification no. 2015-Efectis-R000382

Sponsor Vescom BV

P.O. Box 70 5750 AB DEURNE THE NETHERLANDS

Product name Vescom vinyl wall covering

mass approx. 350 g/m²

Prepared by Efectis Nederland BV

Notified body no. 1234

Author(s) C.C.M. Steinhage B.Sc.

E.O. van der Laan M.Sc.

Project number ENL-15-000073

Date of issue March 2015

Number of pages 5

All rights reserved

No part of this publication may be reproduced and/or published without the previous written consent of Efectis Nederland. Submitting the report for inspection to parties who have a direct interest is permitted.





© 2015 Efectis Nederland BV Page 1 / 5



INTRODUCTION

This classification report defines the classification assigned to Vescom vinyl wall covering, mass approx. 350 g/m^2 in accordance with the procedures given in EN 13501-1:2007+A1:2009.

DETAILS OF CLASSIFIED PRODUCT

2.1 GENERAL

The product, Vescom vinyl wall covering, mass approx. 350 g/m², is defined as a wall covering.

2.2 MANUFACTURER

Vescom BV P.O. Box 70 5750 AB DEURNE THE NETHERLANDS

2.3 PRODUCT DESCRIPTION

According to the sponsor the product is composed of:

Material: vinyl

Mass: approx. 350 g/m2

3. STANDARDS, REPORTS, RESULTS AND CRITERIA IN SUPPORT OF THIS CLASSIFICATION

3.1 APPLICABLE (PRODUCT) STANDARDS

EN 15102:2007 Decorative wall coverings - Roll and panel form products

3.2 REPORTS

Name of Laboratories	Name of sponsor	Report ref. no.	Test method
Efectis Nederland BV	Vescom BV	2015-Efectis-R000380	EN ISO 11925-2:2010
THE NETHERLANDS	THE NETHERLANDS	2015-Efectis-R000381	EN 13823:2014



3.3 TEST RESULTS

Test method and test number	Parameter		No. tests	Results	
				Continuous parameter - mean (m)	Compliance with parameters
EN ISO 11925-2					
surface flame impingement	Fs ≤150 mm	mm		53	-
	Ignition of filter paper			-	Compliant
Edge flame impingement	Fs ≤150 mm		6	43	-
	Ignition of filter paper			-	Compliant
EN 13823					
	FIGRA _{0.2MJ}	[W/s]	3	77	-
	FIGRA _{0.4MJ}	[W/s]		28	-
	THR _{600s}	[MJ]		1.4	-
	LFS < edge			-	Compliant
	SMOGRA	$[m^2/s^2]$		41	-
	TSP _{600s}	[m ²]		40	-
	Flaming debris - flaming ≤ 10 s - flaming > 10 s			-	Compliant Compliant

3.4 CLASSIFICATION CRITERIA

Fire classification of construction products and building elements Excluding floorings and linear pipe thermal insulation products							
Classification criteria							
Class Test method(s)	В	С	D				
EN ISO 11925-2 Exposure = 30 s	$F_s \le 150$ mm within 60 s Ignition of the paper in EN ISO 11925-2 results in a d2 classification.						
EN 13823	FIGRA _{0.2 MJ} \leq 120 W/s LFS $<$ edge of specimen THR _{600s} \leq 7.5 MJ	FIGRA _{0.4 MJ} \leq 250 W/s LFS $<$ edge of specimen THR _{600s} \leq 15 MJ	FIGRA _{0.4 MJ} ≤ 750 W/s				
Additional classification							
Smoke production	$\begin{array}{lll} s1 = & SMOGRA \leq 30 \text{ m}^2/\text{s}^2 \text{ and } TSP_{600s} \leq 50 \text{ m}^2 \text{ ;} \\ s2 = & SMOGRA \leq 180 \text{ m}^2/\text{s}^2 \text{ and } TSP_{600s} \leq 200 \text{ m}^2 \text{;} \\ s3 = & not \text{ s1 or s2} \end{array}$						
Flaming Droplets/particles	d0 = no flaming droplets/ particles in EN 13823 within 600 s; d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s; d2 = not d0 or d1.						



4. CLASSIFICATION AND FIELD OF APPLICATION

4.1 REFERENCE OF CLASSIFICATION

This classification has been carried out in accordance with clause 11 of EN 13501-1:2007+ A1:2009.

4.2 CLASSIFICATION

The product, Vescom vinyl wall covering, mass approx. 350 g/m², in relation to its reaction to fire behaviour is classified:

В

The additional classification in relation to smoke production is:

S¹

The additional classification in relation to flaming droplets / particles is:

d0

Reaction to fire classification: B - s1, d0

4.3 FIELD OF APPLICATION

This classification is valid for the following product parameters:

Mass Approx.. 350 g/m²

This classification is valid for the following end use applications:

Substrate Non-combustible

(class A1/A2 according to EN 13238:2010)

Air gap Not applicable

Methods and means of fixing The wall covering was glued on the substrate

according to the manufacturer's instructions, using

the special adhesive "Vescom 2000"

Joints Vertical joints only

Other aspects of end use

conditions

Wall covering

4.4 DURATION OF THE VALIDITY OF THIS CLASSIFICATION REPORT

There are no limitations in time on the validity of this report.







5. LIMITATIONS

This classification document does not represent type approval or certification of the product.

C.C.M. Steinhage B.Sc.

Project leader reaction to fire

E.O. van der Laan M.Sc. Project leader reaction to fire