

**Vescom BV**  
**Sint Jozefstraat 20**  
**5753 AV Deurne**  
**NEDERLAND**



**Your notice of**  
27-03-2017

**Your reference**

**Date**  
05-05-2017

## Analysis Report 17.01887.09

Required tests :  
**BS 5852 (2006)**

**Clause 11 (upholstery composite) - Assessment of the  
ignitability of upholstered seating - crib ignition source no.  
5**

Identification number	Information given by the client	Date of receipt
T1706721	Yuma 7011	27-03-2017

Gina Créelle

Order responsible

This report may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel.  
The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.  
In assessing compliance with the specifications, we did not take into account the uncertainty on the test results.

**CENTEXBEL • textile competence centre • www.centexbel.be • www.vkc.be**

Inrichting erkend bij toepassing van de besluitwet van 30-01-1947 • Établissement reconnu par application de l'arrêté-loi du 30-01-1947  
GENT • Technologiepark 7 • BE-9052 Zwijnaarde, Belgium • phone +32 9 220 41 51 • fax +32 9 220 49 55 • gent@centexbel.be  
GRACE-HOLLOGNE • Rue du Travail 5 • BE-4460 Grâce-Hollogne, Belgium • phone +32 4 296 82 00 • g-h@centexbel.be  
KORTRIJK • Etienne Sabbelaan 49 • BE-8500 Kortrijk, Belgium • phone +32 56 281828 • fax +32 56 281830 • info@vkc.be  
VAT BE 0459.218.289 • IBAN BE44 2100 4729 6545 • BIC GEBABEBB

Reference: T1706721 - Yuma 7011

**Clause 11 (upholstery composite) - Assessment of the ignitability of upholstered seating - crib ignition source no. 5**

Date of ending the test 05-05-2017  
 Standard used BS 5852 (2006)  
 Deviation from the standard -  
 Conditioning 23°C, relative humidity 50%

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test ; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Water soaking of the cover No  
 Filling SB 36140 (Recticel) \* - fire retardant foam - ± 36 kg/m<sup>3</sup>

\* The filling complies with schedule 1 part 1 of the UK Furniture and Furnishings (Fire) (Safety) Regulations 1988

	1	2
<b>Smouldering criteria</b>		
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Smoulders to extremities	no	no
Smoulders through thickness	no	no
Smoke, heat or glowing more than 1 hour	no	no
Smoulders more than 100 mm from source	no	no
<b>Flaming criteria</b>		
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Flames to extremities	no	no
Flames through thickness	no	no
Flame time >10 min	no	no
Flame time	4 min 25 s	6 min 20 s
	non-ignition - NI/5	non-ignition - NI/5

**Conclusion Non-ignition - NI/5**