



TESTING CERT. #3193.01

Report Number: 17-002078
Revision Number:1
Date Order Received: 07/10/2017

For the Account of: Vescom BV
Sint Jozefstraat 20
NL-5753 AV Deurne

Client's Identification: Faray 8007-8054

CERTIFICATE OF TESTING

TEST PERFORMED: Resistance to Slippage of Yarns in Woven Fabrics Using a Standard Seam ASTM D434-95 as Modified by ASTM D3597-02(2013)

TEST RESULTS

Table with 3 columns: Specimen, Warp Yarn Slippage (lbf), Type of Failure. Includes rows for specimens 1-5 and Avg. Warp, and another section for Specimen, Fill Yarn Slippage (lbf), Type of Failure with specimens 1-5 and Avg. Fill.

ABBREVIATIONS USED

- SB Seam broke before 1/4" slippage - Results should reflect this
SS 1/4" slippage occurred - Note: Actual slippage of yarns is visible
FB Fabric broke before 1/4" slippage - Note: Actual breakage is visible

NOTES

Equipment Used: Tinius Olson H5KT Universal Testing Machine
Seam Description: Per ASTM D3597-02
Seam Type: Standard Lockstitch
Stitches per Inch: 7 -8 stitches per inch
Needle Used: Chrome plated 0.063 inch diameter
Thread: No. 24-4 hard finish Z-twist cotton thread

ACCEPTANCE CRITERIA

A.C.T. Standard: Drapery fabrics over 6oz/sq. yard
Acceptance Criteria: 25 lbs. Minimum

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Handwritten signature in purple ink

Authorized Signature

Date Order Completed: 07/20/2017