

Technical information

Textile Wallcovering IV

November 2011

description

Collection Textile Wallcovering IV is available in various combinations:

technical characteristics*

design	reference	width (cm)	weight (g/m ²)	wood-pulp (%)	polyester (%)
Bora	2520.20 – 2520.49	137	± 161	70	30
Corona	2520.60 – 2520.69	137	± 219	50	50
Oriente	2521.00 – 2521.19	137	± 161	70	30
Classic Luxury	2521.20 – 2521.29	137	± 161	70	30
Pearlized Steel	2520.50 – 2520.54	137	± 241	70	30
Luna Mystique	2520.80 – 2520.84	137	± 241	70	30
Metallic Oriente	2520.90 – 2520.94	137	± 241	70	30
Botanical Engineering	2521.30 – 2521.34	137	± 241	70	30
Crushed Fibres	2521.40 – 2521.49	137	± 241	70	30
Luxiana	2521.60 – 2521.64	137	± 241	70	30
Nazca	2521.70 – 2521.74	137	± 241	70	30
Eternal Rondo	2520.00 – 2520.09	137	± 328	70	30
Venetian Lace (Solid)	2520.10 – 2520.19	137 137	± 292 ± 212	70 70	30 30

Levante (Solid)	2520.70 –	137	± 328	70	30
	2520.79	137	± 212	70	30
Smeralda (Solid)	2521.50 –	137	± 328	70	30
	2521.59	137	± 212	70	30
Chateau Chantilly (Solid)	2521.90 –	137	± 292	70	30
	2521.99	137	± 212	70	30
Pied de Poule (Solid)	2522.10 –	137	± 292	70	30
	2522.19	137	± 212	70	30

fire classification

Fire tests are available on request.

application

Hanging instructions are included in every roll.

adhesive

Only use Vescom adhesive: Vescom 2000 for Textile Wallcovering IV.

maintenance

Vacuum-clean a few times a year (no wet cleaning).

Due to the Lurotex finish, any liquids on the surface can be easily removed with an absorbent material.

* Data given is based on average values (+/- 5 %), unless stated otherwise.