

Application for approval of the trademark  
TREVIRA®

**Trevira**

An International Textures Company

Trevira GmbH  
Markenprüfung /  
Trademark Testing  
Technikum, Gebäude 515  
Max-Fischer-Straße 11  
D-86389 Bobingen

Applicant

Company Vescom B.V.  
Road Sint Jozefstraat 20  
Post Code/City 5753 Deurne  
Country NL

Name / Signature *J.A. Schirmer*  
Schirmer

Trademark Trevira CS

Article Faray

End Use  
Drapes  
Upholstery fabrics

Other uses Bitte umschreiben

Composition 100 % PES

Fabric weight (g/sm) 224

Yarn Details

Warp  
Yarn titre/ count Nm 100/1 CS

Trevira Type --

Yarn supplier TFS

	Weft 1	Weft 2	Weft 3
Yarn titre/ count	Nm 40/2 CS	Nm 70/2 CS	Nm 60/2 CS

Trevira Type --

Yarn supplier HofTex/Lampertsmühle/TFS

Approval: 13.09.2018

(This Trademark approval is valid for a period of 5 years from the date of issue).

The tested article FARAY color creamy/grey with application no. 181029 is granted approval for the trademark Trevira CS for interior use. This article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

The article was tested according to the French Standard NF P 92-504 (Propagation de flamme) and thus also meets the requirements for class M1 according to NF P 92-503, 92-505 and 92-507.

The article was tested according to EN 1101 and thus also meets the requirements for class 1 according to EN 13773.

Thus meets also the requirements according to British Standard BS 5867 part 2 type C.

Thus meets also the requirements for class 1 according to the Italian Standards UNI VF 8456 and UNI VF 8457.

NEN EN ISO 6940/6941: For Trevira CS fabrics no ignition and no rate of flame spread is measured.

This article can meet the requirements according to ÖNORM A 3800-1 part 1, class B1, fume formation class Q 1 and droplet formation class TR1.

This article meets the requirements according to EN 1021 part 1+2 in conjunction with polyurethan foams with a density of more than 30 kg/m<sup>3</sup>.

Thus meets also the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (match) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m<sup>3</sup>).

Thus meets also the requirements according to the Italian standard UNI VF 9175, class 1 IM in conjunction with suitable combustion modified foams.

Thus meets also the requirements according to ÖNORM B 3825 in conjunction with suitable combustion modified foams.

*13.09.2018 J.A. Schirmer*

Trevira GmbH, Trademark Service