

**Ir. Ron Verlouw  
VESCO M BV  
Postbus 70  
NL-5753 AV DEURNE  
NEDERLAND**

**your delivery of**  
2010-07-26

**your reference**

**our reference**  
PVH/7349

**date**  
Zwijnaarde, 2010-08-02

## **Analysis Report 75602/C**

Required tests :

**BS 5852: 2006, clause 11 (upholstery composite)  
Assessment of the ignitability of upholstered seating - crib ignition source no. 5**

Identification number	Information given by the client	Date of receipt
T008351	Vescom Vinyl Upholstery	2010-07-26

Pros Van Hoeyland  
order responsible

For further information, please contact our sectorial adviser Pros Van Hoeyland

This report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel. The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.

our reference	date	page
PVH/7349	2010-08-02	2 / 2

Reference : T008351 - Vescom Vinyl Upholstery

**BS 5852: 2006, clause 11 (upholstery composite)**  
**Assessment of the ignitability of upholstered seating - crib ignition source no. 5**

The following test results relate only to the ignitability of the combination of upholstery composites (BS 5852:2006, clause 11) under the particular conditions of test stated ; they are not intended as a means of assessing the full potential fire hazard of the materials or products in use.

**End of tests:** 2 August 2010

**A. Materials tested**

Cover	:	- quality	Vescom Vinyl Upholstery
		- water soaking	/
Filling	:	- quality	F 35140 (Recticel) *
		- density	fire retardant foam ± 35 kg/m <sup>3</sup>

\* The filling complies with schedule 1 part 1 of the UK Furniture and Furnishings (Fire) (Safety) Regulations 1988

**B. Test results - ignition source crib 5**

	<u>test 1</u>	<u>test2</u>
<u>Flaming criteria</u>		
- unsafe escalating combustion	no	no
- test assembly consumed	no	no
- flames to extremities	no	no
- flames through thickness	no	no
- flame time >10 min	no	no
flame time	4 min 22 s	3 min 55 s
<u>Smouldering criteria</u>		
- unsafe escalating combustion	no	no
- test assembly consumed	no	no
- smoulders to extremities	no	no
- smoulders through thickness	no	no
- smoke/heat/glowing more than 60 min	no	no
- smoulders more than 100 mm from source	no	no
	non-ignition	non-ignition

**Conclusion: non-ignition - NI/5**