

auckland

7071.01 – 7071.34



Kollektion

upholstery

Beschreibung

Bouclé-Möbelstoff in bi-color mit rasterartiger Struktur

Zusammensetzung

76% recycled polyester FR / 24% polyester FR

Breite

± 141 cm, ± 56 inches

Gewicht

± 704 gr/m¹, ± 23 oz/yd¹ fabrics

Brandschutzklasse

EN 1021/1-2

BS 5852, crib 5

NF P 92503-507, M1

NF D 60-013 (AM 18)

DIN 4102, B1

UNI 9175, classe 1.IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

Abrieb

ISO 12947-2

60.000 rubs martindale

ASTM D4157

80.000 double rubs wyzenbeek

Pillingbildung

ISO 12945-2

4 (skala 1-5)

ASTM D3511

5 (skala 1-5)

Reibechtheit

ISO 105-X12

nass 4-5 / trocken 4-5 (skala 1-5)

AATCC 8

nass 5 / trocken 5 (skala 1-5)

Lichtechtheit

ISO 105-B02

6 (skala 1-8)

AATCC 16.3: 40 hours

5 (skala 1-5)

Nahtschiebewiderstand

ISO 13936-2

Kette 3 mm / Schuss 3 mm

ASTM D4034

warp 128 lbs / weft 112 lbs

Reißfestigkeit

ISO 13934-1

Kette 1550 N / Schuss 2500 N

ASTM D5034

warp 220 lbs / weft 402 lbs

Pflege



Schrumpfwerte: Kette -2.4% / Schuss -1.4%




































STANDARD
100

S21-3365
Hohenstein HTTI

auckland

7071.01 – 7071.34

								
7071.01	7071.02	7071.03	7071.04	7071.05	7071.06	7071.07	7071.08	7071.09
								
7071.10	7071.11	7071.12	7071.13	7071.14	7071.15	7071.16	7071.17	7071.18
								
7071.19	7071.20	7071.21	7071.22	7071.23	7071.24	7071.25	7071.26	7071.27
								
7071.28	7071.29	7071.30	7071.31	7071.32	7071.33	7071.34		