

# faray

8058.01 - 8058.18



binder

**curtain 01**

description

**ton sur ton dessin of "swirling" lines in the length**

composition

**100% flame retardant polyester**

width

**± 140 cm, ± 55 inches**

weight

**± 312 gr/m<sup>1</sup>, ± 10 oz/yd<sup>1</sup> fabrics**

visual & thermal comfort

**EN 410/EN 14501**

flame retardancy

**EN 13773, class 1**

**BS 5867-2, type C**

**NF P 92/503-507, M1**

**DIN 4102, B1**

**UNI VF 8456-8457, classe 1**

**IMO 2010 FTP part 7**

**NFPA 701**

**CAN ULC S109**

colorfastness to crocking

**ISO 105-X12**

wet 4-5 / dry 4-5 (scale 1-5)

**AATCC 8**

wet 5 / dry 5 (scale 1-5)

colorfastness to light

**ISO 105-B02**

6-7 (scale 1-8)

**AATCC 16.3: 60 hours**

5 (scale 1-5)

seam slippage

**ASTM D434**

warp 40.5 lbs / weft 58 lbs

care



**shrinkage: warp: -0.2% / weft: -0.2%**



**shrinkage: warp: -0.9% / weft: -0.6%**



**OEKO-TEX®**  
CONFIDENCE IN TEXTILES  
**STANDARD 100**  
S07-0023 HOHENSTEIN HTTI

Tested for harmful substances.  
[www.oeko-tex.com/standard100](http://www.oeko-tex.com/standard100)



International Association of Textile and Apparel Technicians (IATAT)

# faray

8058.01 - 8058.18

---



8058.01



8058.02




8058.03



8058.04



8058.05



8058.06



8058.07




8058.08




8058.09




8058.10




8058.11



8058.12




8058.13




8058.14




8058.15



8058.16



8058.17



8058.18