

malta

7037.01 - 7037.21



binder

upholstery

03

vinyl

description

light spots on a dark font

composition

vinyl coat, cotton/polyester backing

width

± 140 cm, ± 55 inches

weight

backing: ± 110 gr/m², ± 5 oz/yd¹

coating: ± 690 gr/m², ± 31 oz/yd¹

thickness

1.1 mm, 0.04 inches

roll length

± 20 meter, ± 22 yards

flame retardancy

EN 1021/1-2

BS 5852, crib 5

NF P 92/503 - 507, M2

NF D60-013 (AM 18)

DIN 4102, B2

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

abrasion

ISO 12947-2

> 125.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

colorfastness to crocking

ISO 105-X12

wet 5 / dry 5 (scale 1-5)

AATCC 8

wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

8 (scale 1-8)

ASTM D4329: 150 hours

4 (scale 1-5)

resistance to urine

good

resistance to sebum

good

breaking strength

ISO 1421

length 475 N / width 320 N

ASTM D2261

length 7.3 lbs / width 9.2 lbs

flexibility

ISO 5402

> 20.000

adhesion to coating

ASTM D751


length 8.3 lbf / width 5.2 lbf




vinyl  COMMITTED TO SUSTAINABLE DEVELOPMENT

malta

7037.01 - 7037.21



7037.01




7037.02



7037.12



7037.10




7037.06




7037.18



7037.20




7037.17



7037.14




7037.04



7037.05




7037.11




7037.15




7037.03




7037.19




7037.21




7037.16




7037.13



7037.07



7037.08



7037.09