

# lani

7060.01 - 7060.56



binder

**upholstery 02**

description

**tough, felted wool quality in modern applicable colours**

composition

**80% wool / 20% polyamide**

width

**± 140 cm, ± 55 inches**

weight

**± 640 gr/m<sup>1</sup>, ± 21 oz/yd<sup>1</sup> fabrics**

flame retardancy

**EN 1021/ 1-2**

**BS 5852, crib 5 \***

**NF P 92 / 503 - 507, M2 \***

**DIN 4102, B2 \***

**UNI 9175, classe 1 \***

**Cal TB 117**

**NFPA 260, class 1**

**IMO 2010 FTP part 8 \***

\* when FR finished

abrasion

**ISO 12947-2**

250.000 rubs martindale

**ASTM D4157**

100.000 double rubs wyzenbeek

pilling

**ISO 12945-2**

4 (scale 1-5)

**ASTM D3511**

1 (scale 1-5)

colorfastness to crocking

**ISO 105-X12**

wet 4 - 5 / dry 4 - 5 (scale 1-5)

**AATCC 8**

wet 5 / dry 5 (scale 1-5)

colorfastness to light

**ISO 105-B02**

5-7 (scale 1-8)

**AATCC 16.3: 40 hours**

3.5 (scale 1-5)

seam slippage

**ISO 13936 - 2**

warp 2.6 mm / weft 3 mm

**ASTM D4034**

warp 125 lbs / weft 116 lbs

care





# lani

7060.01 - 7060.56

