


leone plus

7054.01 - 7054.26



collection

upholstery
vinyl

description

uni-coloured leather grain

composition

vinyl coat, cotton/polyester backing

width

± 137-140 cm, ± 54-55 inches

weight

backing: ± 110 gr/m², ± 5 oz/yd¹
coating: ± 690 gr/m², ± 31 oz/yd¹

thickness

1.1 mm, 0.04 inches

flame retardancy

EN 1021/1-2
BS 5852, crib 5
NF P 92/503 - 507, M2
NF D60-013 (AM 18)
DIN 4102, B2
UNI 9175, classe 1 IM
Cal TB 117
NFPA 260, class 1
IMO 2010 FTP part 8

abrasion

ISO 12947-2
> 300.000 rubs martindale
ASTM D4157
100.000 double rubs wyzenbeek

colorfastness to crocking

ISO 105-X12
wet 5 / dry 5 (scale 1-5)
AATCC 8
wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02
7 (scale 1-8)
ASTM D4329: 150 hours
4 (scale 1-5)

resistance to blood, urine, sweat and sebum

EN 12720
5 (scale 1-5)

breaking strength

ISO 1421
length 470 N / width 313 N
ASTM D2261
length 7.3 lbs / width 9.2 lbs

flexibility

ISO 7854
400.000 cycles

adhesion to coating

ASTM D751
length 8.3 lbf / width 5.2 lbf



vinyl 
COMMITTED TO
SUSTAINABLE DEVELOPMENT

leone plus


7054.01 - 7054.26




7054.01



7054.02



7054.03



7054.04



7054.05



7054.06




7054.07



7054.08



7054.09



7054.10




7054.11



7054.12




7054.13



7054.14




7054.15



7054.16



7054.17



7054.18



7054.19



7054.20



7054.21



7054.22




7054.23



7054.24



7054.25



7054.26