

dikson

7063.01 - 7063.14



collection

**upholstery
textile**

description

**upholstery fabric with a rich blend of soft
chenille yarns**

composition

**> 40% recycled polyester FR / < 60%
polyester FR**

width

± 140 cm, ± 55 inches

weight

± 819 gr/m², ± 26 oz/yd² fabrics

flame retardancy

EN 1021/ 1-2

BS 5852, crib 5

NF P 92 / 503 - 507, M1

DIN 4102, B1

UNI 9175, classe 1.IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

abrasion

ISO 12947-2

100.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

pilling

ISO 12945-2

4-5 (scale 1-5)

ASTM D3511

5 (scale 1-5)

colorfastness to crocking

ISO 105-X12

wet 4-5 / dry 4-5 (scale 1-5)

AATCC 8

wet 4 / dry 4 (scale 1-5)

colorfastness to light

ISO 105-B02

6 (scale 1-8)

AATCC 16.3: 40 hours

4.5 (scale 1-5)

seam slippage

ISO 13936 - 2

warp 2 mm / weft 2 mm

ASTM D4034

warp 89 lbs / weft 96 lbs

breaking strength

ISO 13934-1

warp 2500 N / weft 1550 N

ASTM D5034

warp 474 lbs / weft 262 lbs

care



shrinkage: warp -2.6% / weft -1.9%




STANDARD
100

S07-0023
Hohenstein HTTI

dikson


7063.01 - 7063.14



7063.01




7063.02



7063.03




7063.04



7063.05



7063.06



7063.07




7063.08



7063.09



7063.10



7063.11



7063.12



7063.13



7063.14