

# furka plus

7064.01 - 7064.44



collection

**upholstery**  
**vinyl**

description

**matt shimmer uni-coloured with fine grain**

composition

**vinyl coat on a cotton/polyester backing**

width

**± 137-140 cm, ± 54-55 inches**

weight

**backing: ± 110 gr/m<sup>2</sup>, ± 5 oz/yd<sup>1</sup>**  
**coating: ± 690 gr/m<sup>2</sup>, ± 31 oz/yd<sup>1</sup>**

thickness

**1.1 mm, 0.04 inches**

flame retardancy

**EN 1021/1-2**  
**BS 5852, crib 5**  
**NF P 92/503 - 507, M2**  
**NF D60-013 (AM 18)**  
**DIN 4102, B2**  
**UNI 9175, classe 1 IM**  
**Cal TB 117**  
**NFPA 260, class 1**  
**IMO 2010 FTP part 8**

abrasion

**ISO 12947-2**  
> 300.000 rubs martindale  
**ASTM D4157**  
100.000 double rubs wyzenbeek

colorfastness to crocking

**ISO 105-X12**  
wet 5 / dry 5 (scale 1-5)  
**AATCC 8**  
wet 5 / dry 5 (scale 1-5)

colorfastness to light

**ISO 105-B02**  
7 (scale 1-8)  
**ASTM D4329: 150 hours**  
4 (scale 1-5)

resistance to blood, urine, sweat and sebum

**EN 12720**  
5 (scale 1-5)

breaking strength

**ISO 1421**  
length 470 N / width 313 N  
**ASTM D2261**  
length 7 lbs / width 9 lbs

flexibility

**ISO 7854**  
400.000 cycles

adhesion to coating

**ASTM D751**  
length 8 lbf / width 5 lbf



**vinyl**   
COMMITTED TO  
SUSTAINABLE DEVELOPMENT

# furka plus

7064.01 - 7064.44

---

