

## jemo

7044.01 - 7044.21



binder

upholstery

03

vinyl

descripción

imagen y estructura similares al textil fino

composición

espuma de vinilo, soporte de algodón/poliéster

ancho

± 140 cm, ± 55 inches

peso

backing: ± 110 gr/m<sup>2</sup>, ± 5 oz/yd<sup>1</sup>coating: ± 690 gr/m<sup>2</sup>, ± 31 oz/yd<sup>1</sup>

espesor

1.1 mm, 0.04 inches

longitud del rollo

± 20 meter, ± 22 yards

combustión retardada

EN 1021/1-2

BS 5852, crib 5

NF P 92/503 - 507, M2

NF D60-013 (AM 18)

DIN 4102, B2

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

resistencia al desgaste

ISO 12947-2

&gt; 300.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

resistencia al frotamiento

ISO 105-X12

wet 5 / dry 5 (scale 1-5)

AATCC 8

wet 5 / dry 5 (scale 1-5)

insensibilidad a la luz

ISO 105-B02

8 (scale 1-8)

ASTM D4329: 150 hours

4 (scale 1-5)

resistencia a la orina

muy buena

resistencia a la grasa

muy buena

resistencia a la tensión

ISO 1421

length 475 N / width 320 N

ASTM D2261

length 7.3 lbs / width 9.2 lbs

flexibles

ISO 7854

400.000

adhesión al revestimiento

ASTM D751

length 8.3 lbf / width 5.2 lbf




vinyl  COMMITTED TO SUSTAINABLE DEVELOPMENT


# jemo

7044.01 - 7044.21


---




7044.01




7044.02




7044.03




7044.04




7044.05



7044.06



7044.07




7044.08




7044.09




7044.10




7044.11




7044.12




7044.13




7044.14



7044.15




7044.16




7044.17




7044.18



7044.19



7044.20



7044.21