

lani

7060.01 - 7060.56



binder

upholstery 02

omschrijving

stoere vervilte wol kwaliteit in moderne toepasbare kleuren

samenstelling

80% wol / 20% polyamide

breedte

± 140 cm, ± 55 inches

gewicht

± 640 gr/m¹, ± 21 oz/yd¹ fabrics

brandwerendheid

EN 1021/ 1-2

BS 5852, crib 5 *

NF P 92 / 503 - 507, M2 *

DIN 4102, B2 *

UNI 9175, classe 1 *

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8 *

* when FR finished

slijtvastheid

ISO 12947-2

250.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

pilling

ISO 12945-2

4 (schaal 1-5)

ASTM D3511

1 (schaal 1-5)

wrijftechtheid

ISO 105-X12

wet 4 - 5 / dry 4 - 5 (schaal 1-5)

AATCC 8

wet 5 / dry 5 (schaal 1-5)

lichtechtheid

ISO 105-B02

5-7 (schaal 1-8)

AATCC 16.3: 40 hours

3.5 (schaal 1-5)

naadschuifweerstand

ISO 13936 - 2

ketting 2.6 mm / inslag 3 mm

ASTM D4034

ketting 125 lbs / inslag 116 lbs

onderhoud





lani

7060.01 - 7060.56

