

dikson

7063.01 - 7063.14



binder

upholstery 02

omschrijving

rijke melange meubelstof van zachte chenille garens

samenstelling

100% brandvertragend polyester

breedte

± 140 cm, ± 55 inches

gewicht

± 819 gr/m¹, ± 26 oz/yd¹ fabrics

brandwerendheid

EN 1021/ 1-2

BS 5852, crib 5

NF P 92 / 503 - 507, M1

DIN 4102, B1

UNI 9175, classe 1.IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

slijtvastheid

ISO 12947-2

100.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

pilling

ISO 12945-2

4-5 (schaal 1-5)

ASTM D3511

5 (schaal 1-5)

wrijfechtheid

ISO 105-X12

nat 4-5 / droog 4-5 (schaal 1-5)

AATCC 8

nat 4 / droog 4 (schaal 1-5)

lichtechtheid

ISO 105-B02

6 (schaal 1-8)

AATCC 16.3: 40 hours

4.5 (schaal 1-5)

naadschuifweerstand

ISO 13936 - 2

ketting 2 mm / inslag 2 mm

ASTM D4034

ketting 89 lbs / inslag 96 lbs

treksterkte

ISO 13937

warp 2500 N / weft 1550 N

ASTM D5034

warp 474 lbs / weft 262 lbs

onderhoud




krimp: ketting -2% / inslag -1.8%



dikson

7063.01 - 7063.14




7063.01




7063.02



7063.03




7063.04




7063.05




7063.06



7063.07



7063.08




7063.09




7063.10



7063.11



7063.12



7063.13



7063.14