

faray

8058.01 - 8058.18



binder

curtain 01

description

ton sur ton dessin of "swirling" lines in the length

composition

100% flame retardant polyester

width

± 55 inches, ± 140 cm

weight

± 10 oz/yd¹, ± 312 gr/m¹ fabrics

visual & thermal comfort

EN 410/EN 14501

flame retardancy

EN 13773, class 1

BS 5867-2, type C

NF P 92/503-507, M1

DIN 4102, B1

UNI VF 8456-8457, classe 1

IMO 2010 FTP part 7

NFPA 701

CAN ULC S109

colorfastness to crocking

ISO 105-X12

wet 4-5 / dry 4-5 (scale 1-5)

AATCC 8

wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.3: 60 hours

5 (scale 1-5)

seam slippage

ASTM D434

warp 40.5 lbs / weft 58 lbs

care



shrinkage: warp: -0.2% / weft: -0.2%



shrinkage: warp: -0.9% / weft: -0.6%



faray

8058.01 - 8058.18



8058.01



8058.02




8058.03



8058.04



8058.05



8058.06



8058.07



8058.08




8058.09




8058.10




8058.11



8058.12




8058.13




8058.14




8058.15



8058.16



8058.17



8058.18