



binder

curtain

组成

100% 阻燃聚酯纤维

宽度

± 140 cm, ± 55 inches

重量

± 297 gr/m¹, ± 10 oz/yd¹ fabrics

温度及视觉舒适度

EN 410/EN 14501

阻燃

EN 13773, class 1

BS 5867-2, type C

NF P 92/503-507, M1

DIN 4102, B1

UNI VF 8456-8457, classe 1

IMO 2010 FTP part 7

NFPA 701

CAN ULC S109

耐擦拭

ISO 105-X12

湿 4-5 / 干 4-5 (由 1— 5)

AATCC 8

湿 5 / 干 5 (由 1-5)

耐褪色

ISO 105-B02

light 6 / dark 6-7 (由 1-8)

AATCC 16.3: 60 hrs

4-5 (由 1-5)

耐滑缝

ISO 13936-2

纵向收缩比 4 mm / 横向收缩比 4 mm

ASTM D434

纵向收缩比 44 lbs / 横向收缩比 52 lbs

额外信息

特别为医疗领域开发和制造



收缩□：纵向收缩比 -1.8% / 横向收缩比 -1.2%



STANDARD
100
S07-0023
Hohenstein HTTI




sindo


8027.01 - 8027.37




8027.03



8027.02




8027.01




8027.05




8027.06




8027.07



8027.11




8027.19




8027.12




8027.04




8027.17




8027.09



8027.13




8027.10




8027.24




8027.21




8027.23



8027.25




8027.36




8027.33




8027.28



8027.22




8027.26




8027.30




8027.27




8027.34



8027.37




8027.35




8027.14



8027.15




8027.18



8027.08




8027.16




8027.20



8027.31



8027.29



8027.32