



binder
curtain

描述
浅色混纺织物

组成
100% 阻燃聚酯纤维

宽度
± 140 cm, ± 55 inches

重量
± 407 gr/m¹, ± 13 oz/yd¹ fabrics

吸声系数
ISO 354
alphaw 0,85 (pleated)

温度及视觉舒适度
EN 410/EN 14501

阻燃
EN 13773, class 1
BS 5867-2, type C
NF P 92/503-507, M1
DIN 4102, B1
UNI VF 8456-8457, classe 1
IMO 2010 FTP part 7
NFPA 701
CAN ULC S109

耐擦拭
ISO 105-X12
湿 4-5 / 干 4-5 (由 1-5)
AATCC 8
湿 5 / 干 5 (由 1-5)

耐褪色
ISO 105-B02
6 (由 1-8)
AATCC 16,3: 60 hrs
5 (由 1-5)

耐滑缝
ISO 13936-2
纵向收缩比 5,5 mm / 横向收缩比 4,7 mm
ASTM D434
纵向收缩比 32 lbs / 横向收缩比 30 lbs



收缩□：纵向收缩比 -2% / 横向收缩比 -1%



收缩□：纵向收缩比 -2,8% / 横向收缩比 2%



STANDARD
100
S07-0023
Hohenstein HTTI



dolin


8048.01 - 8048.09



8048.01




8048.02



8048.03




8048.04



8048.05




8048.06



8048.07



8048.08



8048.09