



binder
curtain

描述
纹理柔软，纱线染色混纺出无方向双色调效果

组成
100% 阻燃聚酯纤维

宽度
± 300 cm, ± 118 inches

重量
± 795 gr/m¹, ± 26 oz/yd¹ fabrics

吸声系数
ISO 354
alphaw 0,80 (pleated)

温度及视觉舒适度
EN 410/EN 14501

阻燃
EN 13773, class 1
BS 5867-2, type C
NF P 92/503-507, M1
DIN 4102, B1
UNI VF 8456-8457, classe 1
IMO 2010 FTP part 7
NFPA 701
CAN/ULC S109

耐擦拭
ISO 105—X12
湿 4-5 / 干 4-5 (由 1—5)
AATCC 8
湿 5 / 干 5 (由 1—5)

耐褪色
ISO 105—B02
6 (由 1—8)
AATCC 16,3: 60 hours
4,5 (由 1—5)

耐滑缝
ISO 13936—2
warp 3,3 mm / weft 3,3 mm
ASTM D434
warp 47 lbs / weft 47 lbs



收缩□：纵向收缩比: -2% / 横向收缩比: -2.9%



STANDARD
100
S07-0023
Hohenstein HTTI



ellis

8079.01 - 8079.13




8079.01




8079.02




8079.03




8079.04




8079.05



8079.06




8079.07



8079.08




8079.09




8079.10



8079.11



8079.12



8079.13