

lani

7060.01 - 7060.56



binder

upholstery

描述

坚韧的羊毛毡品质，配以现代而时尚的色彩

组成

80%羊毛 / 20%聚酰胺

宽度

± 140 cm, ± 55 inches

重量

± 640 gr/m², ± 21 oz/yd² fabrics

阻燃

EN 1021/ 1—2

BS 5852, crib 5 with FR finish

DIN 4102, B2 with FR finish

UNI VF 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

NF D 60-013 - AM18

耐磨性

ISO 12947—2

>300,000 rubs martindale

ASTM D4157

100,000 double rubs wyzenbeek

起毛

ISO 12945—2

4 (由 1—5)

ASTM D3511

2.5 (由 1—5)

耐擦拭

ISO 105—X12

wet 4 — 5 / dry 4 — 5 (由 1—5)

AATCC 8

wet 5 / dry 5 (由 1—5)

耐褪色

ISO 105—B02

5—7 (由 1—8)

AATCC 16.3: 40 hours

3.5 (由 1—5)

耐滑缝

ISO 13936 — 2

纵向收缩比 2.6 mm / 横向收缩比 3 mm

ASTM D4034

纵向收缩比 125 lbs / 横向收缩比 116 lbs

屈伸强度

ASTM D5034

warp 206 lbs / weft 202 lbs





STANDARD
100

S10-0100
Hohenstein HTTI

lani

7060.01 - 7060.56




7060.01



7060.02



7060.03



7060.04



7060.05




7060.06



7060.07



7060.08



7060.09



7060.10



7060.11



7060.12



7060.13



7060.14



7060.15




7060.16




7060.17




7060.18




7060.19




7060.20



7060.21



7060.22



7060.23




7060.24




7060.25



7060.26



7060.27



7060.28



7060.29



7060.30




7060.31



7060.32



7060.33



7060.34



7060.35




7060.36



7060.37



7060.38




7060.39



7060.40




7060.41




7060.42




7060.43




7060.44



7060.45



7060.46




7060.47




7060.48



7060.49




7060.50



7060.51




7060.52




7060.53



7060.54



7060.55



7060.56