

noss

7058.01 - 7058.24



binder

upholstery

描述

软色调混编绳绒面料

组成

100%特弗拉阻燃纤维

宽度

± 140 cm, ± 55 inches

重量

± 904 gr/m¹, ± 29 oz/yd¹ fabrics

阻燃

EN 1021/ 1—2

BS 5852, crib 5

NF P 92 / 503 — 507, M1

DIN 4102, B1

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

耐磨性

ISO 12947—2

70.000 rubs martindale

ASTM D4157

90.000 double rubs wyzenbeek

起毛

ISO 12945—2

4 (由 1—5)

ASTM D3511

5 (由 1—5)

耐擦拭

ISO 105—X12

湿 4 — 5 / 干 4 — 5 (由 1—5)

AATCC 8

湿 5 / 干 5 (由 1—5)

耐褪色

ISO 105—B02

6 — 7 (由 1—8)

AATCC 16,3: 40 hours

5 (由 1—5)

耐滑缝

ISO 13936 — 2

纵向收缩比 3.3 mm / 横向收缩比 3 mm

ASTM D4034

纵向收缩比 77 lbs / 横向收缩比 91 lbs

屈伸强度

ASTM D5034

warp 524 lbs / weft 337 lbs



收缩□：纵向收缩比 -1.5% / 横向收缩比 -1.7%



收缩□：纵向收缩比 -1.6% / 横向收缩比 -3%



STANDARD
100

S07-0023
Hohenstein HTTI

noss

7058.01 - 7058.24



7058.01



7058.02



7058.03



7058.04



7058.05



7058.06




7058.07



7058.08




7058.09



7058.10



7058.11




7058.12



7058.13



7058.14



7058.15



7058.16



7058.17



7058.18



7058.19



7058.20



7058.21



7058.22



7058.23



7058.24