

acton

7062.01 - 7062.39



binder

upholstery

描述

强大的面料产品，有各种泥灰色供选择

组成

87% recycled polyester FR / 13% polyester FR

宽度

± 141 cm, ± 56 inches

重量

± 605 gr/m², ± 20 oz/yd² fabrics

阻燃

EN 1021/ 1—2

BS 5852, crib 5

NF P 92 / 503 — 507, M1

DIN 4102, B1

UNI 9175, classe 1,IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

耐磨性

ISO 12947—2

90,000 rubs martindale

ASTM D4157

100,000 double rubs wyzenbeek

起毛

ISO 12945—2

4 (由 1—5)

ASTM D3511

5 (由 1—5)

耐擦拭

ISO 105—X12

湿 4—5 / 干 4—5 (由 1—5)

AATCC 8

湿 5 / 干 5 (由 1—5)

耐褪色

ISO 105—B02

6 (由 1—8)

AATCC 16,3: 40 hours

4 (由 1—5)

耐滑缝

ISO 13936 — 2

纵向收缩比 3.7 mm / 横向收缩比 3.7 mm

ASTM D4034

纵向收缩比 109 lbs / 横向收缩比 86 lbs

屈伸强度

ISO 13934-1

warp 1380 N / weft 1790 N

ASTM D5034

warp 263 lbs / weft 345 lbs


































收缩□：纵向收缩比 -2.7% / 横向收缩比 -0.6%



STANDARD
100
S07-0023
Hohenstein HTTI

acton

7062.01 - 7062.39

								
7062.01	7062.02	7062.03	7062.04	7062.05	7062.06	7062.07	7062.08	7062.09
								
7062.10	7062.11	7062.12	7062.13	7062.14	7062.15	7062.16	7062.17	7062.18
								
7062.19	7062.20	7062.21	7062.22	7062.23	7062.24	7062.25	7062.26	7062.27
								
7062.28	7062.29	7062.30	7062.31	7062.32	7062.33	7062.34	7062.35	7062.36
								
7062.37	7062.38	7062.39						