

dikson

7063.01 - 7063.14



binder

upholstery

描述

面料系列，由柔软的雪尼尔纱线制成

组成

> 40% recycled polyester FR / < 60% polyester FR

宽度

± 140 cm, ± 55 inches

重量

± 819 gr/m², ± 26 oz/yd² fabrics

阻燃

EN 1021/ 1—2

BS 5852, crib 5

NF P 92 / 503 — 507, M1

DIN 4102, B1

UNI 9175, classe 1,IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

耐磨性

ISO 12947—2

100,000 rubs martindale

ASTM D4157

100,000 double rubs wyzenbeek

起毛

ISO 12945—2

4—5 (由 1—5)

ASTM D3511

5 (由 1—5)

耐擦拭

ISO 105—X12

湿 4—5 / 干 4—5 (由 1—5)

AATCC 8

湿 4 / 干 4 (由 1—5)

耐褪色

ISO 105—B02

6 (由 1—8)

AATCC 16,3: 40 hours

4.5 (由 1—5)

耐滑缝

ISO 13936 — 2

纵向收缩比 2 mm / 横向收缩比 2 mm

ASTM D4034

纵向收缩比 89 lbs / 横向收缩比 96 lbs

屈伸强度

ISO 13934-1

warp 2500 N / weft 1550 N

ASTM D5034

warp 474 lbs / weft 262 lbs



收缩□：纵向收缩比 -2.6% / 横向收缩比 -1.9%




STANDARD
100

S07-0023
Hohenstein HTTI

dikson


7063.01 - 7063.14



7063.01




7063.02



7063.03




7063.04



7063.05



7063.06



7063.07




7063.08



7063.09



7063.10



7063.11



7063.12



7063.13



7063.14